



Joinery Connection Strip - Interior

CONTEGA® IQ makes airtight connections around windows and doors to the interior air barrier. It is a highly flexible, humidity-variable adhesive strip. Multiple adhesive strips allow flexible installation options for masonry or timber frame construction. The tape has slack for expansion to allow for relative motion between components providing a durable seal. CONTEGA® IQ can be plastered or rendered over on the fleece side making excellent integration into surfaces that will be plastered.

- ✓ Effective airtight seal around windows and doors
- ✓ Outstanding adhesion on cold and/or wet surfaces
- ✓ Thin, highly pliable and easily formed around corners and shapes
- ✓ Flexible and expandable to accommodate building movement
- ✓ Airtight connection for the life of the building



20 03 2020



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





Technical Data

Carrier material:	PP fleece and special PP copolymer membrane
Release material:	silicone-coated PE film
Temperature resistance:	long term -40 °C to +90 °C
Installation temperature:	above -10 °C
UV stability and outdoor exposure:	indoor use only
Colour:	dark blue
Storage:	cool and dry (1°C to 20°C)

IMPORTANT INFORMATION

- Thin, highly pliable and easily formed into corners and shapes
- Equipped with an expansion joint to accommodate building movement
- Outstanding adhesion in wet and cold conditions
- Fleece side can be plastered or rendered over

PRODUCT DESCRIPTION

CONTEGA® IQ is a durable vapour-permeable adhesive strip to make effective connections of an interior air barrier assembly to penetrations such as windows and doors. It forms an essential part of a robust interior air barrier system. Made from polypropylene with acrylate adhesive, it has excellent workability and adhesion for effective and durable air seals.

WEATHER EXPOSURE

This product is designed to be installed on building interiors, not in direct sunlight. CONETGA® IQ should be detailed to prevent direct continued sunlight onto the product in service.

APPLICATION NOTES

Before application, substrate should be brushed or wiped clean to provide effective adhesion. Surfaces should be even and smooth enough to provide a clean connection. Surfaces must be free of grease, silicone, and other water repellent substances. The product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and ensure a long-term durable seal.

The bond must not be subjected to tensile strain over time. Any load borne by the product must be transferred to the substrate or other supporting materials as necessary.

Delivery Form				
PRODUCT	ID CODE	LENGTH	WIDTH	QTY
1 self-adhesive strip (for masonry construction)	14897	30 m	90 mm	1
2 self-adhesive strips (for timber construction)	14896	30 m	90 mm	1

