



pro clima TESCON EXTORA® PROFIL

Weathertight Sealing Tape

TESCON EXTORA® PROFIL offers all the benefits of TESCON EXTORA®, with an added split backing for ease of installation. It is a valuable component of weather resistive barrier (WRB) systems requiring connections into corners of window and door installations, or complicated junctions. It is compatible with all pro clima membranes and underlays, as well as rigid sheathings, rigid wall underlays and rigid air barriers (RAB). TESCON EXTORA® PROFIL is weathertight and vapour permeable. It is flexible, easy to cut, and has a 10 / 50 mm split backing release paper, ensuring maximum productivity when things get complicated.

- ✓ Excellent UV resistance (180 days exposure)
- ✓ Long-term durability
- ✓ Highly vapour permeable
- ✓ Outstanding adhesion on cold and/or wet surfaces
- ✓ Weathertight & airtight connections for your WRB



Declare.

NZ



BRANZ Appraised
Appraisal No. 838 [2019]



20 03 2020



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





pro clima TESCON EXTORA® PROFIL

Weathertight Sealing Tape

Technical Data

Carrier Material:	special fleece based on PP	
Release Material:	siliconised paper	
Temperature resistance:	Long term -40 °C to +90 °C	
Installation Temperature:	from -20 °C	
UV stability and outdoor exposure:	180 Days	BRANZ Appraisal No. 838
Colour:	black	
Storage:	cool and dry	

IMPORTANT INFORMATION

- Long term UV exposure before cladding up to 180 days (6 months).
- Thin, highly pliable and easily formed into corners and shapes.
- Outstanding adhesion in wet and cold conditions.

PRODUCT DESCRIPTION

TESCON EXTORA® PROFIL is a UV stabilised, multi-purpose flashing tape which forms a valuable part of your weather resistive barrier (WRB) system. Made from polypropylene (PP) with acrylate it has excellent workability and adhesion for optimal resistance to driving rain at junctions in your WRB layer. The 10 mm split edge backing allows for application at edges and junctions where the tape can be aligned and then fully adhered on a second pass.

WEATHER EXPOSURE

This product is designed to withstand up to 180 days (6 months) direct exposure to UV and still fulfil the intended use for wind and water control for protection against driving rain. Exterior cladding should be detailed to prevent direct sunlight onto TESCON EXTORA® in service.

APPLICATION NOTES

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal. TESCON EXTORA® PROFIL versions come with a 10 mm split backing for ease of application in corners and tricky junctions.

Delivery Form				
ID CODE	LENGTH	WIDTH	BACKING	QTY
15050	30 m	60 mm	10 / 50 split	5
15236	30 m	60 mm	10 / 50 split	20 big pack



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au

