



Multi Conduit Grommet Ø 15-30 mm

Conduit grommet made of strong and highly flexible EPDM for simple, rapid and permanent airtight feed-throughs of up to 9 pipes or conduits through the weather resistive barrier or airtight sealing layer. Complete assembly set for easy installation. Stick with TESCON EXTORA® (8 strips included). For easy sealing of between 1 and 9 pipes or conduits of 15-30 mm in diameter.

- ✓ Complete set for up to 9 pipes
- ✓ Secure bond, quick and secure sealing, indoors or out
- ✓ High-quality EPDM, extremely flexible and elastic
- ✓ Waterproof, suitable for penetrations in façades and roof linings
- ✓ Pipes and cables can be adjusted by pulling or pushing



25 10 2023



Your local NZ support
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

Your local AU support
1800 PRO CLIMA (776 254)
Technical: support@proclima.co.au
General: welcome@proclima.co.au
www.proclima.au





Technical Data

Pipe Size:	Ø 15-30 mm
Material:	EPDM
UV Exposure:	180 Days
Temperature resistance:	long term -40 °C to +150 °C (EPDM)
Installation temperature:	from -10 °C
UV stability and outdoor exposure:	Indoor/outdoor
Colour:	black
Storage:	cool and dry

IMPORTANT INFORMATION

- ROFLEX 20 sealing grommets for between 1 to 9 pipes, Ø 15 – 30 mm.
- Permanent adhesion is achieved with TESCON EXTORA® tapes on all pro clima interior and exterior membranes, other weather resistive barriers and airtight membranes (e.g. those made of PE, PA, PP and aluminium) as well as other underlay/sarking and wall lining membranes (e.g. those made of PP and PET).
- Permanent adhesion is achieved on painted wood, hard plastics and metal (e.g. pipes, windows etc.), hard wood-based panels (chipboard, OSB and plywood panels, MDF board and softwood fibre sub-roof panels).
- Wood fibre sub-roof panels and smooth mineral subsurfaces require pre-treatment with TESCON® PRIMER RP before bonding. Concrete or plaster subsurfaces must not be sandy or crumbling.

PRODUCT DESCRIPTION

ROFLEX 20 multi is a pipe sealing grommet which forms a valuable part of your air barrier system. Made from EPDM with a it has excellent workability for secure and permanent airtight seals where pipe or conduits penetrate membranes, and smooth, non-mineral surfaces.

WEATHER EXPOSURE

This product is designed for use with external weather restive barriers (WRB) systems and internal air barrier systems & will handle up to 180 days direct exposure to UV and still fulfil the intended use for air and water control. Cladding systems should be detailed to prevent direct sunlight onto the EPDM and TESCON EXTORA® in service.

APPLICATION NOTES

Before application, subsurfaces should be brushed off, wiped clean with a cloth or cleaned using compressed air. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded. Subsurfaces must be sufficiently dry and have sufficient bonding capacity.

The best results in terms of bond stability are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases. Pre-treatment with TESCON® PRIMER RP is recommended in the case of subsurfaces with insufficient bonding capacity.

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal.

Delivery Form				
PRODUCT	ID CODE	LENGTH	WIDTH	QTY
ROFLEX 20 multi	12936	200 mm	200 mm	2



Your local NZ support
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

Your local AU support
1800 PRO CLIMA (776 254)
Technical: support@proclima.co.au
General: welcome@proclima.co.au
www.proclima.au

